

A Precision 6" Nom. Swage Press for the production of hose assemblies of all types.

Designed specifically for high production work with rapid operation in the fields of Hydraulic, food and pharmaceutical hose assemblies.

The press has an extremely large opening to provide removal of couplings with large flanges. The Die Sets used are those of a popular European "Pin" design.

2" 2 Wire Hydraulic Hose Capability

6" Industrial Hose Capability

Large Opening

Safety! Will only Swage with Correct Die Set

400 VAC 3 Phase Supply

Automatic Motor Control

Standard swaging range 16 to 78mm diam. Extended swaging range 6.5 to 200mm diam.

UL and CE approvals

Dynamic:

Nom. Size (Industrial Hose Size Inches)	6
Die Set Size (mm nom.)	200-XX
Swaging Range (mm with Std. Die Set)	16 to 78
(mm with Optional Dies)	6.5 to 200
Max. Die Set Opening (mm + Die Set Size)	70
Radial Swaging Force (kN)	1,700
Cycle Speed (Full Stroke-Complete Cycle sec.).	15

Physical:

Dimensions (Plan mm x mm x Height mm)	
60	0 x 420 x 710
Weight (Without Dies & Oil kg)	
Shipping Space (m x m x m)	0.308
Shipping Weight (kg)	230
Crate Size (Plan m x m x Height m)0.72	x 0.55 x 0.78


Electrical:

Supply (Volts / Amps)	400 / 8
Phase (No.)	3
Power (kW)	
Electric Motor Speed (RPM @ 50 Hz)	
Control Power (Volts)	24 VDC


Hydraulic:

nadno.	
Rated Pressure (bar)	300
Pump Flowrate (l/min)(No Load)	11.5
Reservoir Capacity (litres)	60
Filtration (um)	

Installation:



Specifications May Change Without Notice All Dimensions in Millimeters.





Options:

SP200-100 Spacer Set


The SP200-100 Spacer Set allows for the use of more economical Type 50 Die Sets for swaging diameters less than 90mm. For diameters greater than 90mm, the SP200-100 Spacer Set is removed and Type 200 Die Sets are used.

BS50SDS Standard Die Set

11 Die Sets supplied as a package to allow infinite swaging between 16 to 78mm finished swage size. Each Die Set is supplied in a container that will provide for automatic charging of the BS50QCT Quick Change. Tool.




The Extended Range of D	Die Sets Available are as follows:	
50-6.5	6.5 to 8mm finished swage.	
50-8	8 to 10mm finished swage.	
50-10	10 to 12mm finished swage.	
50-12	12 to 14mm finished swage.	
50-14	14 to 16mm finished swage.	
50-76	76 to 84mm finished swage.	
50-84	84 to 90mm finished swage.	
50-90	90 to 100mm finished swage.	
or consult your Dealer for special profile.		




200- Type 200 Die Sets

200-92	92 to 100mm finished swage
200-96	96 to 104mm finished swage
200-102	102 to 112mm finished swage
200-112	112 to 122mm finished swage
200-118	118 to 128mm finished swage
200-122	122 to 132mm finished swage
200-128	128 to 138mm finished swage
200-134	134 to 144mm finished swage
200-145	145 to 155mm finished swage
200-155	155 to 165mm finished swage
	170 to 180mm finished swage
200-180	180 to 190mm finished swage
or consult your Dealer fo	



BSFP Foot Pedal

The Foot Pedal allows the operator to have his hands free while operating the press. It also provides for the press to go into "Fully Automatic" mode with Auto Retract to a specified Open Diameter set on the control panel. Provides for fast/repetitive operation.



Also Consider:

BS-CAPRI Height Adjustable Stand

BS50QCR Quick Change Rack and Magnetic QCT

BS1200DS Depth Stop
BS1200M Mirror

BETASWAGE PTY LTD

A.B.N. 51 090 663 737
38 DRAKE BLVD,ALTONA 3018
P.O. BOX 390 WILLIAMSTOWN
MELBOURNE 3016
PH. 61 - 3 - 9369 0022
FAX. 61 - 3 - 9369 4422
email. sales@betaswage.com.au

web. www.betaswage.com.au